

Freely download the valid and latest test dumps for 100% sure pass

Use our training practice dumps with real exam questions & answers. Freely download the valid test study torrent, and start your preparation with no time wasted. 100% pass guaranteed is our promise. No help, full refund.

All Products Contact now

Why Choose Us



Quality and Value

DumpsTests Practice Exams are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development - no all dumps.



Tested and Approved

We are committed to the process of vendor and third party approvals. We believe professionals and executives alike deserve the confidence of quality coverage these authorizations provide.



Easy to Pass

If you prepare for the exams using our DumpsTests testing engine, it is easy to succeed for all certifications in the first attempt. You don't have to deal with all dumps or any free torrent / rapidshare all stuff.



Try Before Buy

DumpsTests offers free demo of each product. You can check out the interface, question quality and usability of our practice exams before you decide to buy.

As a busy-working man I have no time and heart to prepare so I purchase braindumps for CPIM-SMR. I pass exam just one day's preparation. Great!



Laura



Try Before You Buy

Download a free sample of any of our exam questions and answers

- ✓ 24/7 customer support, Secure shopping site
- ✓ Free One year updates to match real exam scenarios
- ✓ If you failed your exam after buying our products we will refund the full amount back to you.

Free Demo Download

59728

CUSTOMERS

59728

DOWNLOADS

59728

TEAM MEMBERS

59728

SHARES

<http://www.torrentvce.com>

Pass the Actual Test with the Latest Vce Torrent at first attempt

Exam : LOT-922

Title : Developing IBM Lotus Domino 8.5.2
Applications: Advanced XPage
Design

Vendors : IBM

Version : DEMO

NO.1 Aaron has created an XPages application that has a couple of XPages to surface the same data to two different application roles in two completely different user interfaces. Each role can manipulate parts of the data, but in both cases, the data must adhere to the same business logic and rules. What would be the best way for Aaron to implement the same business logic in each XPage.?

- A. Create a common Client-Side JavaScript Library for the XPages to share that the user interface can use to execute the business logic
- B. Use a series of Custom Controls to hold the business logic and share them amongst the XPages
- C. Create a common Server-Side JavaScript Library for the XPages to share that the user interface can use to execute the business logic
- D. The user interface and the business logic in an XPage can not easily be separated and must be maintained in each XPage

Answer: C

NO.2 John has a JavaScript function in a Client Side JavaScript library which he wrote to parse some JSON data and loop through the resulting objects. If he wanted to perform the same task in Server Side JavaScript what would be the most efficient action?

- A. write a new function in Server Side JavaScript to perform the same task
- B. copy the Client Side function into a Server Side JavaScript library, add the script library to his XPage and call the function from his Server Side JavaScript
- C. add the Client Side JavaScript library to his XPage and call the function from his server side JavaScript
- D. Server Side JavaScript does not work with JSON data

Answer: B

NO.3 Lydia wants to create a JSON string to represent an array with three objects. Each object has two variables, vA and vB, set to different string values of "one", "two", "three", "four", "five", and "six". What is

the proper syntax for the JSON string?

- A. [{ vA: 'one', vB: 'two' }, { vA: 'three', vB: 'four' }, { vA: 'five', vB: 'six' }]
- B. "[{ vA: 'one', vB: 'two' }, { vA: 'three', vB: 'four' }, { vA: 'five', vB: 'six' }]"
- C. "[{ vA: one, vB: two }, { vA: three, vB: four }, { vA: five, vB: six }]"
- D. new Array(new Object({ vA: 'one', vB: 'two' }), new Object({ vA: 'one', vB: 'two' })), new Object({ vA: 'one', vB: 'two' }));

Answer: B

NO.4 Dominic wants to implement the open source CSS framework called Blueprint in his XPages application.

He does not want to include any other CSS framework resources which may exist on the Domino server.

What is the best way to include all of the required CSS files in the XPages in his application?

- A. In each XPage in the application add the required CSS files to the Resources section
- B. Create a new theme which extends webstandard and then add each Blueprint CSS file via a resource definition
- C. Create a new theme which extends oneui and then add each Blueprint CSS file via a resource definition
- D. Create a new theme which does not have an extension property and then add each Blueprint CSS file via a resource definition

Answer: D

NO.5 Ernie wants to add the Dojo theme "soria" to the other styling on his XPage. Which theme code will add

the appropriate class to the body tag of the outputted HTML?

- A. <control>
<name>ViewRoot</name>
<property mode="override"
>
<name>styleClass</name>
<value>soria</value>
</property>
<control>
- B. <control>

```
<name>ViewBody</name>
<property mode="override"
>
<name>styleClass</name>
<value>soria</value>
</property>
<control>
C. <control>
<name>ViewRoot</name>
<property mode="concat"
>
<name>styleClass</name>
<value>soria</value>
</property>
<control>
D. <control>
<name>ViewBody</name>
<property mode="concat"
>
<name>styleClass</name>
<value>soria</value>
</property>
<control>
```

Answer: C

NO.6 Rick creates a Server-Side JavaScript library, and defines a few global variables at the beginning of the

library. The JavaScript in his XPage and in the JavaScript library modify those global variables. The server the application runs on is heavily used, and the application settings are set to Keep

Pages on Disk for best scalability. When the application executes, what is likely to happen?

- A. The application will perform as expected.
- B. The application will generate an error because you can not declare global Server-Side JavaScript variables
- C. The application will run, but the values of the globally defined variables may be lost when the server's JVM garbage collects variables, causing unexpected results.
- D. The application will run, but every partial or full refresh will reset the values of the global

variables when it reloads the Server-Side JavaScript library.

Answer: C

NO.7 Frank is attempting to add some functionality to an existing XPage: ?The XPage has a Date Time

Picker edit box named "graduationDate" where users must enter their graduation date.

?Frank looks at

the HTML source of the XPage and sees that the edit box has the HTML attribute:

dojoType="ibm.xsp.widget.layout.DateTimeTextBoxContainer" ?Frank has added a combo box where

users should choose their type of Job, from the options "Intern", "Graduate" or "Experienced".

?Frank

wants to add an onchange listener to the combo box, that checks the value of the graduation date and

gives a browser alert popup dialog like "Intern and Graduate positions only available in the first 2 years

after graduation". ?Frank has looked at the HTML source of the XPage and sees that the Date Time

Picker edit box has a dojoType attribute. Which of the following code snippets should Frank use to

retrieve the graduation date before triggering the alert dialog:

A. var graduationDate = getComponent("graduationDate").getValue();

B. var graduationDate = XSP.getElementById("#{id:graduationDate}").value;

C. var graduationDate = dojo.byId("#{id:graduationDate}").value;

D. var graduationDate = dijit.byId("#{id:graduationDate}").getValue();

Answer: D

NO.8 Liz wants to make the user confirm their action when they try and delete a document from the

application using a delete button. The confirmation message needs to display the title of the document in

it. What is the best way to compute this message?

A. In the client side event of the delete button use the following code:

```
if (confirm("Are you sure you want to delete the document "
```

```
+
```

```
document1.getItemValueString('title'))
```

```
{
```

```
return true;
```

```
}else{  
return false;  
}
```

B. In the client side event of the delete button use the following code:

```
if (confirm("Are you sure you want to delete the document "  
+  
"#{javascript:document1.getItemValueString('title')}"))  
{  
return true;  
}else{  
return false;  
}
```

C. In the server side event of the delete button use the following code:

```
if (confirm("Are you sure you want to delete the document "  
+  
document1.getItemValueString('title')))  
{  
return true;  
}else{  
return false;  
}
```

D. In the server side event of the delete button use the following code:

```
if (confirm("Are you sure you want to delete the document "  
+  
"#{javascript:document1.getItemValueString('title')}"))  
{  
return true;  
}else{  
return false;  
}
```

Answer: B

NO.9 Elizabeth needs to parse the contents of a web page held on a remote server into an applicationScope variable via the server side onclick event of a button using Server Side JavaScript. How would she do this?

A. It is not possible to perform network operations from Server Side JavaScript

B. Create a new Java class to perform the operation in a Java Script Library and call it from the onclick

event of the button.

C. Create a new Java class to perform the operation in a Java Agent and call it from the onclick event of the button.

D. Create a new Java class to perform the operation in the WebContent\WEB-INF\src folder via the Package Explorer and call it from the onclick event of the button.

Answer: D

NO.10 Jo wants to make a configurable list of countries available to the client side JavaScript of her XPage for

use in various different fields on the web page. What would be the most efficient approach?

A. Add an @DbColumn to a server side script library to look up the country list in each place it is required

B. Perform an AJAX request to get the country list from another XPage when it is required using dojo.xhrGet

C. Use the Output Script control to create a global Client Side JavaScript object to reference when the list is required

D. Add a @Decorum to a client side script library to look up the country list in each place it is required

Answer: C